

PENDING CLAIMS AS AMENDED

Please amend the claims as follows:

1. (currently amended) A method for pre-coding in a communication system, comprising:
determining pre-coder parameters;
pre-coding first data in accordance with said determined pre-coder parameters, wherein the step of pre-coding first data in accordance with said determined parameters comprises pre-coding dedicated pilot data;
transmitting said pre-coded first data; and
transmitting non pre-coded first reference data on a common pilot signal, wherein the common pilot signal is sent on a separate channel from the pre-coded first data.
2. (original) The method as claimed in claim 1 wherein determining a pre-coder parameters comprises:
receiving a reference data; and
determining the pre-coder parameters in accordance with said received reference data and the reference data.
3. (original) The method as claimed in claim 1 wherein determining a pre-coder parameters comprises:
receiving the non pre-coded first reference data;
determining the pre-coder parameters in accordance with said received non pre-coded first reference data and the first reference data; and
transmitting said determined pre-coder parameters.
4. (original) The method as claimed in claim 3 further comprising:
receiving said determined pre-coder parameters; and
providing said determined pre-coder parameters to the pre-coder.

5. (currently amended) The method as claimed in claim 1 wherein pre-coding first data in accordance with said determined parameters comprises:

pre-coding a payload data; and
~~pre-coding a dedicated pilot data.~~

6. (original) The method of claim 1 wherein said transmitting a non pre-coded reference data comprises:

transmitting a continuous non pre-coded reference data.

7. (original) The method of claim 1 wherein said transmitting a non pre-coded reference data comprises:

transmitting a discontinuous non pre-coded reference data.

8. (original) The method of claim 1 wherein said transmitting a non pre-coded reference data comprises:

transmitting a pilot data.

9. (currently amended) The method as claimed in claim 1, further comprising:

receiving the non pre-coded first reference data with at least two antennae;
equalizing each of said received non pre-coded first reference data by with at least two equalizers to an equalizer and provide equalized non pre-coded first reference data;

determining the pre-coder parameters by adjusting characteristics of the at least two equalizers in accordance with the received non pre-coded first reference data and the first reference data; and

transmitting said determined pre-coder parameters.

10. (original) The method as claimed in claim 9 wherein said determining the pre-coder parameters by adjusting characteristics of the at least two equalizers in accordance with the received non pre-coded first reference data and the first reference data comprises:

optimizing a quality metric of a composite data comprising the equalized non pre-coded first reference data.

11. (currently amended) A method for demodulating pre-coded data in a communication system, comprising:

receiving a reference data and a pre-coded data, wherein the reference data comprise pre-coded dedicated pilot signal data;

receiving non pre-coded reference data on a common pilot signal, wherein the common pilot signal is received on a separate channel from the pre-coded data;

determining demodulator parameters in accordance with said received reference data and said received non pre-coded reference data; and

demodulating the pre-coded data in accordance with said determined demodulator parameters.

12. (canceled)

13. (canceled)

14. (original) The method as claimed in claim 11 wherein the reference data are continuous reference data.

15. (original) The method as claimed in claim 11 wherein the reference data are discontinuous reference data.

16. (currently amended) An apparatus for pre-coding in a communication system, comprising:

a pre-coder configured to pre-code first reference data in accordance with pre-coder parameters;

a first transmitter communicatively coupled to said pre-coder configured to:

transmit the pre-coded data; and

transmit ~~[[a]]~~ non pre-coded ~~first~~ second reference data on a common pilot signal, wherein the common pilot signal is sent on a separate channel from the pre-coded data.

17. (original) The apparatus as claimed in claim 16, further comprising:

a first receiver communicatively coupled to said pre-coder configured to receive a reference data;

a first processor communicatively coupled to said first receiver; and

a storage medium communicatively coupled to said first processor and containing a set of instructions executable by the processor to:

determine the pre-coder parameters in accordance with said received reference data and the reference data.

18. (currently amended) The apparatus as claimed in claim 16, further comprising:

a second receiver configured to receive the non pre-coded ~~first~~ second reference data;

a second processor communicatively coupled to said second receiver;

a storage medium communicatively coupled to said first processor and containing a set of instructions executable by the processor to:

determine the pre-coder parameters in accordance with said received ~~[[non]]~~ pre-coded first reference data and the non pre-coded ~~first~~ second reference data; and

a second transmitter communicatively coupled to said second processor configured to transmitting said determined pre-coder parameters.

19. (currently amended) The apparatus as claimed in claim 18, wherein said ~~first~~ second receiver is further configured to:

receive said determined pre-coder parameters; and

provide said received pre-coder parameters to said pre-coder.

20. (canceled)

21. (currently amended) The apparatus as claimed in claim 16 wherein said first transmitter is further configured to transmit the non pre-coded ~~first~~ second reference data continuously.
22. (currently amended) The apparatus as claimed in claim 16 wherein said first transmitter is further configured to transmit the non pre-coded ~~first~~ second reference data discontinuously.
23. (currently amended) The apparatus of claim 16 wherein said non pre-coded ~~first~~ second reference data comprise a pilot data.
24. (currently amended) The apparatus as claimed in claim ~~20~~ 16 wherein said first transmitter is further configured to transmit the pre-coded ~~second~~ first reference data continuously.
25. (currently amended) The apparatus as claimed in claim ~~20~~ 16 wherein said first transmitter is further configured to transmit the pre-coded ~~second~~ first reference data discontinuously.
26. (currently amended) The apparatus of claim ~~20~~ 16 wherein said pre-coded ~~second~~ first reference data comprise a dedicated pilot data.
27. (currently amended) The apparatus as claimed in claim 16, further comprising:
at least two equalizers configured to accept the received non pre-coded ~~first~~ second reference data and provide equalized non pre-coded ~~first~~ second reference data;
a processor communicatively coupled to said at least two equalizers;
a storage medium communicatively coupled to the processor and containing a set of instructions executable by the processor to determine said pre-coder parameters by adjusting characteristics of the at least two equalizers in accordance with the received non pre-coded ~~first~~ second reference data and the pre-coded first reference data; and
a second transmitter communicatively coupled to said processor configured to transmit the determined pre-coder parameters.

28. (currently amended) The apparatus as claimed in claim ~~16~~ 27 wherein said processor determines said pre-coder ~~characteristics~~ parameters by adjusting characteristics of the at least two equalizers in accordance with the non pre-coded ~~first~~ second reference data and the pre-coded first reference data by executing a set of instructions to:

optimize a quality metric of a composite data comprising the equalized non pre-coded ~~first~~ second reference data.

29. (currently amended) An apparatus for demodulating pre-coded data, comprising:
a first receiver configured to:

receive a pre-coded reference data and a pre-coded payload data;

receive non pre-coded reference data on a common pilot signal, wherein the common pilot signal is received on a separate channel from the pre-coded data; and

determine demodulator parameters in accordance with said received pre-coded reference data and said non pre-coded reference data; and

a demodulator communicatively coupled to said receiver configured to demodulate the pre-coded payload data in accordance with said determined demodulator parameters.

30. (canceled)

31. (original) The apparatus as claimed in claim 29 wherein the reference data comprise a pre-coded pilot signal.

32. (original) The apparatus as claimed in claim 29 wherein the reference data are continuous reference data.

33. (original) The apparatus as claimed in claim 29 wherein the reference data are discontinuous reference data.

34. (currently amended) A digital signal processing apparatus for pre-coding in a communication system, comprising:

memory storage unit; and

a digital signal processor communicatively coupled to said memory storage unit, and capable of executing instructions to:

determine pre-coder parameters;

pre-code first data in accordance with the determined pre-coder parameters, wherein the first data comprise second reference data and payload data; and

assist in preparing the pre-coded first data and non pre-coded first reference data for transmission, the non pre-coded reference data prepared for transmission on a common pilot signal, wherein the common pilot signal is sent on a separate channel from the pre-coded first data.

35. (currently amended) A digital signal processing apparatus for demodulating pre-coded data in a communication system, comprising:

memory storage unit; and

a digital signal processor communicatively coupled to said memory storage unit, and capable of executing instructions to:

accept a pre-coded reference data and a pre-coded payload data;

accept non pre-coded reference data from a common pilot signal, wherein the common pilot signal is received on a separate channel from the pre-coded data;

determine demodulating parameters in accordance with the accepted pre-coded reference data and said non pre-coded reference data; and

demodulate the pre-coded payload data in accordance with the determined demodulating parameters.

36. (currently amended) An apparatus for pre-coding in a communication system, comprising:

means for determining a pre-coder parameters;

means for pre-coding first data in accordance with said determined pre-coder parameters,
wherein the first data comprise pre-coded dedicated pilot signal data;

means for transmitting said pre-coded first data and a non pre-coded first reference data,
the non pre-coded first reference data transmitted on a common pilot signal, wherein the common
pilot signal is sent on a separate channel from said pre-coded first data.

37. (currently amended) An apparatus for demodulating pre-coded data, comprising:

means for receiving a pre-coded reference data and a pre-coded payload data;

means for receiving non pre-coded reference data on a common pilot signal wherein the
common pilot signal is received on a separate channel from the pre-coded data;

means for determining demodulator parameters in accordance with said received pre-
coded reference data and said non pre-coded reference data; and

means for demodulating the pre-coded payload data in accordance with said determined
demodulator parameters.

38. (new) A method for pre-coding in a communication system, the method comprising:

pre-coding predetermined data in accordance with a set of pre-coder parameters to obtain
a first pilot burst of pre-coded predetermined data;

transmitting over a communication link the first pilot burst to a destination station;

transmitting over the communication link a second pilot burst to the destination station,
wherein the second pilot burst comprises non pre-coded predetermined data.

39. (new) The method as claimed in claim 38, further comprising:

receiving, from the destination station, an estimate of characteristics of the
communication link; and

adjusting the set of pre-coder parameters in accordance with the estimate.